



Report No. : CESMSDS190207001

Material Safety Data Sheet

材料安全数据表

Name of Sample: Li-ion Battery
产品名称 : 锂离子电池

Model Specification:
产品型号 : BC LINK

Client: FUJIAN BELFONE COMMUNICATIONS TECHNOLOGY CO., LTD
委托单位 : 福建北峰通信科技股份有限公司

国家轻工业电池及储能材料质量监督检测中心
先进储能材料国家工程研究中心有限责任公司检测中心
National Light Industry Quality Supervision and Testing Center of Battery Energy Storage Materials
Test Center of Advanced National Engineering Research Center of Storage Materials



说 明

Marking

1. 报告无“检测报告专用章”或“检测单位公章”无效。
The test report is invalid without “Special seal for inspection report” or “Inspection official seal “of Test Center.
2. 复制报告未重新加盖“检测报告专用章”或“检测单位公章”无效。
The copied report is invalid without restamping the "special seal for inspection report" or "inspection official seal".
3. 报告无批准人、审核人和主检人签名无效。
The test report is invalid without the signatures of Approver, Reviewer and Testing engineer.
4. 报告涂改无效。
The test report is invalid if altered.
5. 对检测报告若有异议，应于收到报告之日起十五天内向检测单位提出。
Objections to the test report must be submitted to Test Center within 15 days.
6. 报告仅对送检样品负责。
The test report is Valid for the tested samples only.
7. 本报告检测结论中“N/A”表示“不适用”，“P”表示“符合标准要求”，“F”表示“不符合标准要求”。
As for test result, "N/A" means is “not applicable”, “P” means “pass”, “F” means “fail”.

检测单位地址：广东省深圳市宝安区新安街道宝石路29号蓝坤集团大厦B栋1楼

Lab Address: 1/F, Lankun Group Building B, No.29, Baoshi road, Xin'an Street, Bao'an District, Shenzhen City, Guangdong Province, China

电话(TEL): 0755-22678989-8069

传真(FAX): 0755-22678299


邮政编码(Post Code): 518101


E-mail: ces_sztc@corun.com


Material Safety Data Sheet

材料安全数据表

Section 1——Chemical Product and Company Identification			
化学品及企业标识			
Product Name 产品名称:	Li-ion Battery 锂离子电池		
Type/Mode 样品型号:	BC LINK (3.7V 2200mAh 8.14Wh)		
Commissioned by: 委托单位:	FUJIAN BELFONE COMMUNICATIONS TECHNOLOGY CO., LTD 福建北峰通信科技股份有限公司		
Commissioner address: 委托单位地址:	A15, Huaqiao Economic Development Zone, Shuangyang, Luojiang District, Quanzhou City, Fujian 福建省泉州市洛江区双阳华侨经济开发区 A15 北峰电讯科技园		
Manufacturer: 生产单位:	FUJIAN BELFONE COMMUNICATIONS TECHNOLOGY CO., LTD 福建北峰通信科技股份有限公司		
Inspection according to 鉴定依据	EEC Directive 93/112/EC UN "Recommendations on the TRANSPORT OF DANGEROUS GOODS" 联合国《关于危险品货物运输的建议书》		
Emergency telephone call 应急电话	0595-22788271		
接样日期	2019-01-25	签发日期	2019-02-07

 Approved by: 

 Reviewed by: 

 Tested by: 

Section 2. Composition/information on Ingredient

成分/组成信息

Chemical Name 化学品名称	Chemical Formula 化学式	CAS No. CAS 号	Composition 成份 (in % by weight) (重量百分比)
Cobalt acid lithium 钴酸锂	LiCoO ₂	12190-79-3	40~44
Graphite 石墨	C	7782-42-5	30~32
Electrolyte 电解液	---	---	11~13
Aluminum Foil 铝箔	Al	7429-90-5	2~4
Copper Foil 铜箔	Cu	7440-50-8	5~7
Polypropylene 聚丙烯	(C ₃ H ₆) _n	9003-07-0	1~2

Section 3. Hazards Identification

危险性概述

Explosive risk 爆炸危险性	This article does not belong to the explosion dangerous goods 该物品不属于爆炸危险品
Flammable risk 易燃危险性	This article does not belong to the flammable material 该物品不属于易燃危险品
Oxidation risk 氧化危险性	This article does not belong to the oxidation of dangerous goods 该物品不属于氧化危险品
Toxic risk 毒害危险性	This article does not belong to the toxic dangerous goods 该物品不属于毒害危险品
Radioactive risk 放射危险性	This article does not belong to the radiation of dangerous goods 该物品不属于放射危险品
Mordant risk 腐蚀危险性	This article does not belong to the corrosion of dangerous goods 该物品不属于腐蚀危险品
Other risk 其他危险性	This article is Polymer Lithium Battery Watt hour rate 16.28Wh, which belong to the Lithium ion batteries. 该物品为聚合物锂电池，瓦时率16.28Wh，属于锂离子电池。

Section 4. First aid measures

急救措施

Eye: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

眼睛: 万一接触，立即用大量的清水冲洗至少 15 分钟，翻起上下眼睑，直到化学的残留物消失为止，迅速就医。

Skin: Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get

medical aid.

皮肤: 万一接触, 用大量水冲洗至少 15 分钟, 同时除去污染的衣物和鞋子, 迅速就医。

Inhalation: Remove from exposure and move to fresh air immediately. Use oxygen if available.

吸入: 立即从暴露处移至空气清新处, 如果呼吸困难给予输氧, 立即就医。

Ingestion: Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious.

Call a physician

食入: 饮用两杯牛奶或水。如果当事人仍然清晰可以采取催吐的方法, 并且立即就医。

Section 5. Fire-fighting measures

消防措施

Flash Point: N/A.

燃点: 不适用

Auto-Ignition Temperature: N/A.

自燃温度: 不适用

Extinguishing Media: Water, CO₂.

灭火介质: 大量水 (降温), 二氧化碳

Special Fire-Fighting Procedures: Self-contained breathing apparatus.

特殊灭火程序: 自给式呼吸器

Unusual Fire and Explosion Hazards: Cell may vent when subjected to excessive heat-exposing battery contents.

异常火灾或爆炸: 当电芯暴露于过热的环境中时, 安全阀可能会打开。

Hazardous Combustion Products: Carbon monoxide, carbon dioxide, lithium oxide fumes.

燃烧产生的危险物品: 一氧化碳, 二氧化碳, 锂氧化物烟气

Section 6. Accidental release measures

泄露应急处理

Steps to be taken in case Material is Released or Spilled If the battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. Wipe it up with a cloth, and dispose of it in a plastic bag and put into a steel can. The preferred response is to leave the area and allow the battery to cool and vapors to dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.

为防止电池材料泄露或释放采取的措施如果电池内部材料泄露, 试验人员应立刻撤离试验区直到烟气消散。将通风设备打开吹散危险性气体。用抹布擦净试验区, 清除溢出的液体, 将泄露电池放进塑料袋中, 然后放进钢制容器。避免皮肤和眼睛接触或吸入有害气体。

Waste Disposal Method: It is recommended to discharge the battery to the end, to use up the metal lithium inside the battery, and to bury the discharged battery in soil..

废弃物处置方法: 建议将电池完全放电, 消耗电池内部的锂金属, 并且深埋于土壤中。

Section 7. Handling and storage

操作处置和储存

The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.

禁止打开、毁坏或焚烧电池，因为电池有可能在这些处理过程中发生爆炸、破裂或泄露等事故。禁止将电池短路、过充、强制放电或扔入火中。禁止挤压刺穿电池或将电池浸入溶液中。

Precautions to be taken in handling and storing Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

操作处置和储存中的防范措施禁止物理或电滥用，禁止高温储存，最好将电池储存在阴凉、干燥、通风及温度变化较小的环境中。禁止将电池接触加热设备或将电池直接暴露与阳光中。

Other Precautions The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity

其他要注意的防范措施拆解、挤压、直接放入火中或高温条件下，电池可能发生爆炸和燃烧。禁止短接或将电池正负极错误的安装在设备中。

Section 8. Exposure controls/personal protection

接触控制/个人防护

Respiratory Protection In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores. Respiratory Protection is not necessary under conditions of normal use.

呼吸防护：

当电池排气阀打开时，应尽量使通风设备开至最大，避免将打开排气阀的电芯局限在某一狭窄空间内。正常操作条件下，呼吸保护是不必要的。

Ventilation Not necessary under conditions of normal use.

通风条件 正常使用条件下不必考虑。

Protective Gloves Not necessary under conditions of normal use.

防护手套 正常使用条件下不必考虑。

Other Protective Clothing or Equipment Not necessary under conditions of normal use.

其他防护服装或设备 正常使用条件下不必考虑。

Personal Protection is recommended for venting battery Respiratory Protection, Protective Gloves, Protective Clothing and safety glass with side shields.

电池开阀试验时应做好个人防护呼吸防护，防护手套，防护服装和有护边的安全玻璃罩都是要准备的。

Section 9. Physical and chemical properties

物理和化学特性

Appearance: Square

外形：方形

Ref, No.: CESUN190207001

认证编号：CESUN190207001

Odour: If leaking, smells of medical ether

气味：泄漏时，有刺激性气味。

pH: Not applicable as supplied.

酸碱度：不适用

Flash Point: Not applicable unless individual components exposed.

闪点：针对单个组分暴露情况，其他不适用。

Flammability: Not applicable unless individual components exposed.

易燃度：针对单个组分暴露情况，其他不适用。

Relative density: Not applicable unless individual components exposed.

相对密度：针对单个组分暴露情况，其他不适用。

Solubility (water): Not applicable unless individual components exposed

溶解性（水溶性）：针对单个组分暴露情况，其他不适用。

Solubility (other): Not applicable unless individual components exposed.

溶解性（其他）：针对单个组分暴露情况，其他不适用。

Section 10. Stability and reactivity

稳定性和反应活性

Stability: Product is stable under conditions described in Section

稳定性：产品在第7节所述的条件下稳定。

Conditions to Avoid : Heat above 70°C or incinerate. Deform. Mutilate. Crush. Disassemble. Overcharge. Short circuit. Expose over a long period to humid conditions.

应避免的条件：加热 70°C 以上或焚烧、变形、毁坏、粉碎、拆卸、过充电、短路，长时间暴露在潮湿的条件下。

Materials to avoid: Oxidising agents, alkalis, water.

应避免的材料：氧化剂，碱，水。

Hazardous Decomposition Products : Toxic Fumes, and may form peroxides.

危险分解物：有毒烟雾，并可能形成过氧化物。

Hazardous Polymerization : N/A.

聚合危害：不适用

If leaked, forbidden to contact with strong oxidizers, mineral acids, strong alkalies, halogenated hydrocarbons.

如果发生泄露，避免与强氧化剂，无机酸，强碱，卤代烃接触。

Section 11. Toxicological information

毒理学资料

Signs & symptoms: None, unless battery ruptures.

标志及症状：无，除非电池破裂。

In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.

内部物质暴露的情况下，蒸汽烟雾可能对眼睛和皮肤的刺激性。

Inhalation: Lung irritant.

吸入：对肺有刺激性。

Skin contact: Skin irritant.

皮肤接触：对皮肤刺激性。

Eye contact: Eye irritant

眼睛接触：对眼睛有刺激性。

Ingestion: Poisoning if swallowed.

食入：吞下中毒。

Medical conditions generally aggravated by exposure: In the event of exposure to internal contents, moderate to severe irritation, burning and dryness of the skin may occur, Target organs nerves, liver and kidneys.

下列情况下会危险人员身体健康：如果与电池内部材料直接接触，皮肤可能会出现干燥、灼烧等轻微或严重的刺激，并且损坏靶器官的神经，肝脏和肾脏。

Section 12. Ecological information

生态学资料

Mammalian effects: None known at present.

对哺乳动物的影响：目前未知。

Eco-toxicity: None known at present.

生态毒性：目前未知。

Bioaccumulation potential: Slowly Bio-degradable

生物体内积累：慢慢地生物降解。

Environmental fate: None known environmental hazards at present.

环境危害：目前没有已知的环境危害。

Section 13. Disposal consideration

废弃处置

Do not incinerate, or subject cells to temperature in excess of 70°C, Such abuse can result in loss of seal leakage, and/or cell explosion. Dispose of in accordance with appropriate local regulations.

禁止焚烧，或使电池温度超过70°C，这种滥用可导致泄漏和/或电池爆炸。应按照相应的地方性法规处理。

Section 14. Transport information

运输信息

Label for conveyance: Lithium Battery Label., Class 9 Label, Cargo Aircraft Only

运输标签：锂电池标签，或第九类危险品标签，或仅限货机标签

UN Number: 3480&3481

UN 编号：3480&3481

Packaging Group: N/A

包装等级：不适用

Marine pollutant: No

海洋污染物：无

Proper Shipping name: Lithium Ion Batteries(Including Lithium Polymer Batteries) , Lithium Ion Battery Packed With Equipment, Lithium Ion Battery Contained In Equipment

正确的装运名称: 锂离子电池(包括锂聚合物电池), 或锂离子电池与设备包装在一起, 或锂离子电池安装在设备中

运输信息: 锂聚合物电池已通过联合国《试验和标准手册》第III部分 38.3 小节相应测试要求, (报告编号: CESUN190207001)。

锂离子电池瓦时额定值不超过 100Wh 或者锂离子电芯瓦时额定值不超过 20Wh, 根据第 60 版 DGR 手册 965 第 II 节/第 IB 节或 966~967 第 II 节的指令可以运输。

包装应坚固足以避免在运输, 处理和堆放期间的机械损坏。选择合适的包装材料和包装设计, 要防止电池意外导电和端子腐蚀。

Transport information: Lithium Polymer battery is of a type proved to meet the Requirements of each test in the UN MANUAL OF TESTS AND CRITERIA, Part III ,sub-section 38.3 (Report No. : CESUN190207001)

The lithium-ion battery with a watt-hour rating not exceeding 100Wh or the cell with the watt-hour rating is not exceeding 20Wh, The lithium-ion battery according to Section II/Section IB of PACKING INSTRUCTION 965, or Section II of PACKING INSTRUCTION 966~967 of the Dangerous Goods regulations 60th Edition may be transported.

The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

Section 15 Regulation information

法规信息

Law information

法律信息

《Dangerous Goods Regulations》

《危险物品规则》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《对危险货物运输的有关规定的建议》

《International Maritime Dangerous Goods》

《国际海运危险货物规则》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《危险品安全运输技术指令》

《Classification and code of dangerous goods》

《危险货物分类和品名编号》

《Occupational Safety and Health Act》 (OSHA)

《职业安全卫生法》

《Toxic Substance Control Act》 (TSCA)

《有毒物质控制法》

《Consumer Product Safety Act》 (CPSA)

《消费产品安全法》

《Federal Environmental Pollution Control Act》 (FEPCA)

《联邦环境污染控制法》

《The Oil Pollution Act》 (OPA)

《石油污染法案》

《Superfund Amendments and Reauthorization Act Title III (302/311/312/313)》(SARA)

《超级基金修正案和再授权法案 III(302/311/312/313)》

《Resource Conservation and Recovery Act》(RCRA)

《资源保护及恢复法案》

《Safety Drinking Water Act》(CWA)

《安全饮用水法》

《California Proposition 65》

《加州 65 提案》

《Code of Federal Regulations》(CFR)

《美国联邦法规》

In accordance with all Federal, State and local laws

根据所有联邦、州和地方法律。

Section 16 Other information

其他信息

This file is only effective to the Battery(model BC LINK) provided by commissioner FUJIAN BELFONE COMMUNICATIONS TECHNOLOGY CO., LTD which manufactured by FUJIAN BELFONE COMMUNICATIONS TECHNOLOGY CO., LTD The commissioner provides the composition information of batteries, and promises its integrity and accuracy. Users should read this file carefully, and use the batteries in correct method. Test Center of Advanced National Engineering Research Center of Storage Materials doesn't assume responsibility for any damage or loss because of misuse of batteries.

本文件仅对由委托方（福建北峰通信科技股份有限公司）提供的，并由福建北峰通信科技股份有限公司生产的电池 (BC LINK) 型号有效。该电池的成分信息由委托方提供并承诺其完整性和准确性。用户应仔细阅读此文件，并按照正确的方法使用电池，如因电池使用不当造成的损害或损失，先进储能材料国家工程研究中心有限责任公司检测中心（CES）不承担任何责任。

-- End of Report --